



ABP Series Aluminum Boom Poles

Owner's Manual



Overview

Removable tip

The custom removable tip allows for easy drop-through cable insertion and makes conversion or cable replacement quick and uncomplicated.

Ergonomic Twist Locks

The ergonomic twist locks are comfortable to grip and make length adjustment fast and effortless.

Sturdy lightweight aluminum

The sturdy lightweight aluminum construction withstands the rigors of road use while maintaining flawless telescoping.

Anti-twist alignment tubing

The anti-twist alignment makes one-handed unlocking of all twist locks effortless. One turn of the wrist and all sections smoothly extend to the desired length.

Strain Relief

The strain relief attachment absorbs tension and protects the cable from the edges of the tip exit.

Coiled XLR Cable

The integrated coiled XLR cable smoothly extends and retracts with the telescoping tubes (on select models).

Attaché XLR connector

Attaché XLR connectors are manufactured by Rean®, a trademark of Neutrik® (on selected models).

Solderless design

With solderless design, no special tools are needed to add or replace the XLR cable with the cable conversion/replacement kit (sold separately).

Bottom-exit XLR connector

The bottom-exit XLR connector is securely housed in the bottom threaded cap (on select models).

Introduction

Thank you for choosing Auray.

The Auray ABP series Boom Pole is a lightweight and durable solution for Electronic News Gathering (ENG), Electronic Field Production (EFP), documentary, and other field recording applications. By placing the microphone close to the subject while remaining at a distance or out of frame, the ABP series Boom Pole will save you time and effort.

Instructions

1. While firmly holding the boom pole, loosen the twist locks and extend the sections.
2. Once extended to the desired length, securely tighten the twist locks.
3. To collapse the boom pole, loosen all twist locks and return the sections to their minimized position. Once the boom pole is collapsed, re-tighten the locks.

Note: The anti-twist alignment design makes it possible to loosen all the twist locks at the same time.

While firmly holding the boom pole, grasp all of the twist locks with one hand and loosen them all with one motion. Once the twist locks are loosened, tip the boom pole downward, and the sections should slide to their fully-extended positions.

Recommended Accessories

BPB-34: Auray Neoprene Boom Pole Bag

BPH: Auray Boom Pole Holder

DUSM-1: Auray Universal Shock Mount

Available Parts and Accessories

ABC-35: Cable replacement kit for APB-35B

ABC-66: Cable replacement kit for APB-66B

ABC-47: Cable replacement kit for APB-47B

ABC-59: Cable replacement kit for APB-59B

ABC-412: Cable replacement kit for APB-412B

Specifications

Min/Max Length Comparison	ABP-35		ABP-66		ABP-47		ABP-59		ABP-412	
	ABP-35N	ABP-35B	ABP-66N	ABP-66B	ABP-47N	ABP-47B	ABP-59N	ABP-59B	ABP-412N	ABP-412B
Model	ABP-35N	ABP-35B	ABP-66N	ABP-66B	ABP-47N	ABP-47B	ABP-59N	ABP-59B	ABP-412N	ABP-412B
Min Length	2.2' .7 m	2.2' .7 m	1.7' .5 m	1.7' .5 m	2.3' .7 m	2.3' .7 m	2.4' .7 m	2.4' .7 m	3.5' 1.1 m	3.5' 1.1 m
Max Length	5.3' 1.6 m	5.3' 1.6 m	6.3' 1.9 m	6.3' 1.9 m	7.3' 2.2 m	7.3' 2.2 m	9.3' 2.8 m	9.3' 2.8 m	12.3' 3.8 m	12.3' 3.8 m
Weight	.8 lb. .36 kg	1.1 lb. .5 kg	1.45 lb. .66 kg	1.6 lb. .73 kg	1.2 lb. .55 kg	1.45 lb. .66 kg	1.65 lb. .75 kg	1.9 lb. .86 kg	1.6 lb. .73 kg	1.9 lb. .86 kg
Sections	3	3	6	6	4	4	5	5	4	4
Cable	N	Y	N	Y	N	Y	N	Y	N	Y

Precautions

- Please read and follow these instructions, and keep this manual in a safe place.
- Handle the product with care.
- Keep fingers clear of the telescoping joints when adjusting length.
- Use only parts provided by the manufacturer.
- Make sure the item is intact and that there are no missing parts.
- All photos are for illustrative purposes.

Three-Year Limited Warranty

This AURAY product is warranted to the original purchaser to be free from defects in materials and workmanship under normal consumer use for a period of three (3) years from the original purchase date or thirty (30) days after replacement, whichever occurs later. The warranty provider's responsibility with respect to this limited warranty shall be limited solely to repair or replacement, at the provider's discretion, of any product that fails during normal use of this product in its intended manner and in its intended environment. Inoperability of the product or part(s) shall be determined by the warranty provider. If the product has been discontinued, the warranty provider reserves the right to replace it with a model of equivalent quality and function.

This warranty does not cover damage or defect caused by misuse, neglect, accident, alteration, abuse, improper installation or maintenance. EXCEPT AS PROVIDED HEREIN, THE WARRANTY PROVIDER MAKES NEITHER ANY EXPRESS WARRANTIES NOR ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. This warranty provides you with specific legal rights, and you may also have additional rights that vary from state to state.

To obtain warranty coverage, contact the Auray Customer Service Department to obtain a return merchandise authorization ("RMA") number, and return the defective product to Auray along with the RMA number and proof of purchase. Shipment of the defective product is at the purchaser's own risk and expense.

For more information or to arrange service, visit www.aurayaudio.com or call Customer Service at 212-594-2353.

Product warranty provided by the Gradus Group.
www.gradusgroup.com

AURAY is a registered trademark of the Gradus Group.
© 2014 Gradus Group LLC. All Rights Reserved.



GG2



For distance microphone placement on ENG and EFP recording projects

Manufactured with sturdy lightweight aluminum for portability and reliability

Smooth telescoping for easy expansion and length adjustment

Ergonomic twist locks and anti-twist alignment for effortless setup

Designed for solderless adding or replacement of coiled XLR cable

Integrated XLR cable with Attaché connectors manufactured by Rean®, a trademark of Neutrik® (on selected models).