

### SunBriteDS Digital Signage

# **MODEL** DS-3214TSP

#### **DISPLAY**

AVAILABLE COLORS



Silver



Black



SHOWN IN BLACK

### **KEY FEATURES**

- 32" Pro Series True Outdoor All-Weather LED Touch Screen.
- Dispersive Signal (3-M Microtouch) Touch Screen Technology.
- Portrait installation only, for landscape installation use DS-3214TSL.
- High temperature Enhanced Solar Tolerance (EST) technology prevents isotropic blackout.
- Exterior designed to protect internal components from rain, insects, dust, humidity and salt air.
- Multi-fan airflow system keeps the unit cool & dry in temperatures up to 122 degrees F.
- Ability to operate in cold weather (-40 degrees F).
- Powder-coated aluminum exterior.
- Weatherproof detachable 20 WATT speaker module (not included).
- Weatherproof remote control, weatherproof control buttons.
- Innovative water-tight Cable Entry System seals out moisture, allows for easy hook-ups.
- Rear IR receiver (located in cable-entry compartment).
- RS232 serial control with discrete on, off, and input control.



# **MODEL** DS-3214TSP

**SCREEN** 

LED SCREEN

32-inch diagonal TFT Active Matrix

RESOLUTION

1920 x 1080 Full-HD 1080p

ASPECT RATIO

16:9

CONTRAST RATIO

1300:1

FRAME RATE 60 Hz

TOUCH SCREEN TECHNOLOGY

3M Dispersive Signal Technology -

single touch

VIEWING ANGLE

176° x 176°

RESPONSE TIME 22 milliseconds

TV FORMATS

1080p,1080i, 720p, 480p, 480i

SCREEN ORIENTATION Portrait Mode

**CONNECTIONS** 

RF

Antenna/CATV (ATSC/QAM/NTSC) x1

HDMI

HDMI™ Input x2

VIDEO COMPOSITE

S-Video x1 and Composite Video x1,

L/R Audio Inputs x1

VIDEO COMPONENT

YPbPr plus Stereo Audio x2

PC

15-pin D-sub VGA plus Stereo Audio

**CONTROL SET** 

RS232 Serial, Discrete IR Control,

Concealed IR Window

AUDIO OUT

SPDIF, Analog 1/8" Headphone Jack

SPEAKERS

20 WATT detachable, optional speaker

module (not included).

INPUT POWER

100-240 VAC, 50-60 Hz 2.5 A Max

USB Type "B" jack for Microtouch HID

Touch interface

TEMPERATURE TOLERANCES

OPERATING TEMP

-40° to 122° F. (-40° to 50°C.)

NON-OP. TEMP

-40° to 140° F. (-40° to 60°C.)

(OFF MODE WITH POWER APPLIED)

The non-operating temperature feature requires power to be applied.

PHYSICAL SPECS

ACCESSORIES INCLUDED

Weatherproof remote control

**EXTERIOR** 

Powder-coated aluminum

EXTERIOR COLORS
Black, Silver

TV DIMENSIONS

 $20.07"W \times 32.07"H \times 6.29"D$  (with

optional speaker module)

TV WEIGHT

41.6 lbs. or 44.5 lbs. with optional

speaker module

SHIPPING DIMENSIONS

37.0"W x 32.0"H x 12.0"D

SHIPPING WEIGHT

75.0 lbs.

RESIDENTIAL WARRANTY

Two-year parts & labor

COMMERCIAL WARRANTY

Two-year parts & labor

**VESA MOUNT** 

100mm x 100mm or 400mm x 200mm