

# Airport TakeOff Instructions

ph: 866.55THINK (558.4465) fax: 707.527.0808

3636 North Laughlin Road, Suite 170, Santa Rosa, CA 95403

**thinkTANK**® photo

Be Ready "Before The Moment"™

## Deploying Backpack Straps



**Step 1:** Completely unzip the panel covering the backpack straps.



**Step 2:** Pull the panel down and under the wheel housings at the bottom of the bag.



**Step 3:** Tightly seal the panel in place with the hook and loop, just behind the foot stand underneath the bag.



**Step 4:** Untuck the backpack straps from the pocket and adjust as needed for proper fit. Reinsert the backpack straps into the pocket to use the backpack as a rolling bag. Closing the covering panel is not necessary. The Airport TakeOff can still be effectively used as a rolling bag while the panel is open.

## Extendable Handle



Open the zipper flap on top of the Airport TakeOff to reveal the extendable handle. To raise the handle, **press and hold** the button on the middle of the handle and simultaneously raise the handle completely. The release button must always be held down for the handle to be fully extended or retracted.

## Adjustable Sternum Strap



The sternum strap adjusts up and down, along the blue rails on the backpack straps.

## Security Cable and Lock



The cable and lock are inside the clear pocket, underneath the front flap on the Airport TakeOff. They are used to secure an optional laptop slip case, such as the Artificial Intelligence 15 or 17, when it is stored in the front pocket.

## Setting the Lock Combination



The lock combination default setting is 0-0-0. To reset the combination, use a pen to press the small release button, on the side of the lock, until it clicks. Release the button and set the desired 3 digit combination. Be sure that each digit is centered precisely in the spaces. Press the locking clasp inward until it clicks to confirm the new combination.

## Carrying a Tripod or Monopod



**Step 1:** A tripod or monopod can be carried on the side of the Airport TakeOff by using the straps and tripod cup included with the bag. The tripod cup is only necessary to use for tripods with bulky leg releases. The stretchable side pocket on the Airport TakeOff can fit two legs of tripods with compact leg releases, instead of attaching the tripod cup.



**Step 2:** Insert the tripod straps horizontally, above and below the triglide buckle that is fixed on the side of the Airport TakeOff. There is hook and loop on each tripod strap and the corresponding placement slot to prevent the straps from sliding out, when unclipped.



**Step 3:** The tripod cup attaches to the fixed triglide buckle on the side of the Airport TakeOff. Thread the open end of the tripod cup strap, up through the triglide.



**Step 4:** To secure the tripod cup in place, double over the loose end of the strap and insert it into the bottom side of the triglide.



**Step 5:** A monopod can be carried in the stretchable side pocket and stabilized near the top of the bag with the included monopod strap.