

# Pixel Racing Harness V2.0 Instructions

ph: 866.55THINK (558.4465) fax: 707.527.0808

3636 North Laughlin Road, Suite 170, Santa Rosa, CA 95403

**thinkTANK** photo

Be Ready "Before The Moment"

## Attachment to the FRONT of the belt



This is the correct harness position, as viewed from the front. The harness can be adjusted in the front and back after attachment to the belt. **FOR STEROID SPEED BELT:** Attach clips around metal D-rings on belt.

## Attachment to the BACK of the belt



This is the proper harness position, as viewed from the back. The harness should be positioned 2 -3" below the neck. **FOR STEROID SPEED BELT:** Attach rear clip around metal D-ring on the back of the belt.



**Step 1:** The shoulder straps can be connected on the belt anywhere towards the front of the body. Unclip the buckle, then wrap it behind and under the belt. Insert the female side of the buckle through the horizontal webbing on the belt.



**Step 2:** Clip the buckle together to secure in place. Then use the front buckles at the bottom of the shoulder strap padding to adjust for proper length and weight distribution.



**Step 1:** Connect the rear harness strap in a similar way as the front straps. To keep the harness properly centered, insert the buckle through the webbing loop with the Think Tank logo on it.



**Step 2:** To adjust the length of the rear strap, use the buckle located below the mesh. The rear buckle and two similar front buckles are used to fine tune weight distribution on the belt and harness.